



# CR 500 600

Vertical display cooler



+2/+7°C 

**D**



**CR 500**  
667 x 620 x 2018  
477lt

**C**



**CR 600**  
667 x 716 x 2018  
567lt



## Advantages

- Ideal for the conservation and promotion of bottled and packed products.
- Top cooling capacity ideal for perishable products.
- Selected by leading companies in the dairy and beverage sector
- Ideal for heavy duty and outdoors use
- Shelving solutions suitable for each customer's needs.
- Reliable and functional
- Optimum product visibility.
- Plug ready



## Basic Equipment

- Hi efficiency compressor
- Digital controller
- EMD - Energy Management Device
- EBD - electronic fan motor (evaporator)
- Self closing doors
- LED Internal lighting
- Operation switch
- Four castors
- 5 adjustable reinforced shelves
- Special antidazzle double glass
- Easily removable grill
- Air cooled condenser
- Two regulators
- Automatic defrost
- Drainage
- Internal body from non toxic pre painted steel sheet



## Optional Equipment

- Shelves
- Product labeling and price tags
- EBD electronic fan motor (compressor)
- Branding
- Remote Controller:
  1. Online temperature (The temperature of the device is available on the mobile device of the user through the app or the e-mail)
  2. Temperature history (The user has access to the temperature history of the device through the app)
  3. Alarm (The user receives an alarm on the mobile device in the unlikely event of power failure or malfunction of the device)
  4. Export reports to PDF or CSV (Excel).



## Technical Specifications

| TECHNICAL SPECIFICATIONS      | UNITS  | CR 500           | CR 600           |
|-------------------------------|--------|------------------|------------------|
| External dimensions (lxwxh)   | mm     | 667 x 620 x 2018 | 667 x 716 x 2018 |
| Internal dimensions (lxwxh)   | mm     | 587 x 510 x 1593 | 587 x 566 x 1593 |
| Packing dimensions (lxwxh)    | mm     | 680 x 657 x 2104 | 680 x 752 x 2104 |
| Internal gross volume         | lt     | 477              | 567              |
| Capacity of 330ml cans        | pcs    | 636              | 812              |
| Temperature range             | °C     | +2 / +7          | +2/+7            |
| Energy consumption            | kW/24h | 2,290            | 2,070            |
| Gross / net weight            | kg     | 106.5 / 101      | 115.5 / 108      |
| Climate class                 | -      | CC2/K2           | CC2/K2           |
| Pieces per truck 13.6m        | -      | 60               | 57               |
| Pieces per 20/40'ft container | -      | 24 / 54          | 24 / 51          |
| Refrigeration                 | -      | AIR COOLED       | AIR COOLED       |
| Refrigerant                   | -      | R290/R600a       | R290/R600a       |

\*The energy consumption concerns specific metrics

